53541.013.0549.213.8120.5

Maximum Power (Pmax/W)	Operating Voltage (Vmpp/V)	53040.013.0549.213.7620.3	Short-Circuit Current (Isc/A)	Module Efficiency ηm(%)

Performance at NMOT

Maximum Power (Pmax/W)	Operating Voltage (Vmpp/V)	Open-Circuit Voltage (Voc/V)	Short-Circuit Current (Isc/A)

STC: Irradiance 1000W/m , Cell Temperature 25°C, Air Mass AM1.5NMOT: Irradiance at 800W/m , Ambient Temperatue 20°C, Air Mass AM1.5, Wind Speed 1m/s

Electrical characteristics with different rear side power gain (refer to 540W front)

Pmax gain	Pmax/WVmpp/V	Voc/V	Monocrystalline

Cell Dimensions	Weight	Module Dimensions	Cable Cross Section Size	Front Glass	No. of Bypass Diodes	Frame
					TD7672M/540W	
		144 (6*24)	32.5kg (71.5lbs.)	2300*1135*35mm (90.55*44.68*1.38inches)		

TUV: 4mm (0.006inches)/UL: 12AWG

2.0mm (0.08 inches) AR Coating Semi-tempered Glass 2.0mm (0.08 inches) Glazed Semi-tempered Glass

Maximun System Voltage	Maximun Series Fuse	Static Loading	Conductivity at Ground	
				1500V/D



: i i =

Portrait 300mm/Landscape 1200mm/Customized cable length

Temperature Coefficient Pmax	-0.36%/°C
Temperature Coefficient Voc	-0.26%/°C
	+0.043%/°C
NMOT	43±2°C

HVSHFLILFDWLRDGNHIHDWUHVGHVFULEHGLWKLVGDWDVKHHWPDGHYLDWHVOLKWODGDUHWDUDWHHGHWRRRLLRYDWLRHKDFHPHWKRDOHVRDUHFKRLHV&RWGUHVHUYHVWKHULKWWRPRGLFDWLRGHVFULEHG

TALESUN