


BIPRO

TD7G78M **156 half-cell**

570 - 590W

10BB half-cut mono perc



KEY FEATURES



10BB half-cut cell technology

<2% (1st year) / ≤0.45% (Linear)



Industry leading high yield

Bifacial PERC cell technology,
5%-25% more yield depends on different conditions



Excellent Anti-PID performance

2 times of industry standard Anti-PID test by TUV SUD



Wider application

No water-permeability and high wear-resistance,
can be widely used in high-humid, windy and dusty area



IP68 junction box

High waterproof level

SYSTEM & PRODUCT CERTIFICATES

- IEC 61215 / IEC 61730 / UL 61730
- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environment Management System
- ISO 45001: 2018 Occupational Health and Safety Management Systems




PERFORMANCE WARRANTY

12

30

Linear Performance



ELECTRICAL PARAMETERS

Performance at STC (Power Tolerance 0 ~ +3%)

Maximum Power (Pmax/W)	570	575	580	585	590
Operating Voltage (Vmpp/V)	45.1	45.2	45.3	45.4	45.5
	12.65	12.73	12.81	12.89	12.97
Open-Circuit Voltage (Vo /V)	53.5	53.6	53.7	53.8	53.9
Short-Circuit Current (Isc/A)	13.38	13.46	13.54	13.62	13.70
Module Efficiency η (%)	20.1	20.3	20.5	20.7	20.9

Performance at NMOT

Maximum Power (Pmax/W)	420	424	427	431	435
Operating Voltage (Vmpp/V)	41.9	42.0	42.1	42.2	42.3
	10.03	10.10	10.16	10.22	10.28
Open-Circuit Voltage (Vo /V)	50.0	50.1	50.2	50.3	50.4
Short-Circuit Current (Isc/A)	10.79	10.85	10.91	10.98	11.04

STC: Irradiance 1000W/m², Cell Temperature 25°C, Air Mass AM1.5 NMOT: Irradiance at 800W/m², Ambient Temperature 20°C, Air Mass AM1.5, Wind Speed 1m/s

Electrical characteristics with different rear side power gain (refer to 580W front)

Pmax gain	Pmax/W	Vmpp/V	Isc/A	Voc/V	Efficiency (%)
5%	609	45.3	13.45	53.7	14.22
10%		45.3	14.09	53.7	14.89
15%	667	45.3	14.73	53.7	15.57
20%	696	45.3	15.37	53.7	16.25
25%	725	45.3	16.01	53.7	16.93

MECHANICAL SPECIFICATION

Monocrystalline	
Cell Dimensions	156 (6*26)
Weight	35kg (77.2lbs.)
Module Dimensions	2471*1134*35mm (97.28*44.65*1.38inches)
Cable Length ()	Portrait 300mm/Landscape 1200mm/Customized
Cable Cross Section Size	TUV: 4mm (0.006inches)/UL: 12AWG
	2.0mm (0.08 inches) AR Coating Semi-tempered Glass
	2.0mm (0.08 inches) Glazed Semi-tempered Glass
No. of Bypass Diodes	31pcs/carton, 558pcs/40hq
	USA) 31pcs/carton, 496pcs/40hq
Junction Box	


OPERATING CONDITIONS

Maximum System Voltage	1500V/DC(IEC)
	-40°C ~ +85°C
Maximum Series Fuse	30A
Static Loading	Snow Loading: 5400Pa/ Wind Loading: 2400Pa
Conductivity at Ground	0.1
	100M
	T01/LJQ-3-CSY/MC4/MC4-EVO2
*Under STC: Backside Output Ratio = $P_{max(rear)} / P_{max(front)}$	70% ± 5%

TEMPERATURE COEFFICIENT

Temperature Coefficient Pmax	-0.36%/°C
Temperature Coefficient Voc	-0.26%/°C
	+0.043%/°C
NMOT	43±2°C

I-V CURVE



TECHNICAL DRAWINGS

